



## “Guzzler Jr.”



- Ideal for portable handwash stations
- Angled pump face for ease of operation from a standing position
- Accommodates 1/4" - 1/2" hose
- 1.3 GPM
- Available with standard or heavy-duty stainless steel spring
- Optional Quick-connect TrueSeal™ fittings for ease of installation
- Umbrella valves to maintain prime

### Specifications / Options

<b>Pump Body*</b>	Acrylonitrile-Butadiene-Styrene (ABS)
<b>Clamp Ring</b>	Stainless Steel
<b>Valves*</b>	Umbrella (EPDM)
<b>Diaphragm*</b>	Natural Rubber
<b>I/O Flange Cartridges*</b>	PVC
<b>Internal Spring*</b>	Standard (Std), Heavy-Duty (HD) (all stainless steel)
<b>Fittings*</b>	Acetal w/Nitrile O-Ring for TrueSeal fittings / Nylon for Barbed fittings

\* In contact with fluid

### End Connectors



Front view of pump with Quick Connect TrueSeal fittings for ease of use with 3/8" hose



Top view of pump with barbed end fittings available for a range of hose sizes

## Guzzler® Foot Pump GF-0250S

### Performance

<b>Flow Rate</b>	Per minute <sup>1</sup> : 1.3 Gal (5.8L) Per stroke: 2.8 oz (83 mL)
<b>Max Head</b>	12 ft (3.6 m)
<b>Max Lift</b>	2.5 ft (0.76 m) (Std spring) 4.2 ft (1.3 m) (HD spring)
<b>Max Pressure</b>	7 psi (0.4 kg/cm <sup>2</sup> )
<b>Max. Service Temp</b>	140°F (60°C)

<sup>1</sup>: with std spring

### Available Ports

	in	1/4	5/16	3/8	1/2
	cm	0.64	0.79	0.95	1.27
<b>TrueSeal™ Quick Connect Fittings</b>				S	
<b>NPT Female (Tapped)</b>		•			
<b>Tapped with Barbed Fittings</b>		•	•	•	•

S Standard • Optional

### Valves





**Umbrella** — Most efficient for pumping clean liquid. Also used for air and vacuum service.

### Stainless Steel Spring Options



Standard (Std) — 18 lb/in  
Heavy Duty — 25 lb/in



	in	cm
<b>A</b>	4-3/8	11.1
<b>B</b>	2-3/4	7.0
<b>C</b>	15°	
<b>D</b>	2-1/8	5.4
<b>E</b>	3-1/2	8.9
<b>F</b>	4	10.2
<b>Mounting Holes</b>	1/4	0.64
<b>Weight</b>	0.55 lb	0.25 kg

TrueSeal™ is a trademark of Parker-Hannifin Corporation.

930 Waterman Avenue  
East Providence, RI 02914  
(401) 438-1110 • fax (401) 438-2713  
toll-free (888) 438-1110 • www.thebosworthco.com

Guzzler® and Sea-lect® are trademarks of The Bosworth Company.



# Guzzler® Foot Pump GF-0250S



**Example: GF-0250S-086-09-2929-10**

- Guzzler Foot Pump
- Model style #0250S: Polystyrene Body, Same Side Ports
- EPDM Umbrella Valves
- Natural Rubber Diaphragm
- 3/8" Quick Connect ends
- Standard weight Spring

